



HAVEN

"REDIFINING
AFFORDABLE
HOUSING"

SPECIFICATION BOOK

Cecelia Kominsky
G6 THESIS

PROJECT TITLE: HAVEN		
PROJECT No: MASTER THESIS		
LOCATION IN PROJECT FLOORING	ITEM REFERENCE # 0301 BEIGE	
MANUFACTURER: GERFLOR	AMOUNT/QUANTITY: 2 m roll	DATE: 12/4/2024
CONTACT: Our offices are open Monday to Friday from 8:30 am to 12:30 pm and from 1:30 pm to 5:30 pm. Call us at 02. 90.40.10.	APPLICATION: Mipolam Classic 2 mm in the 0301 Beige color is designed for a variety of commercial applications, particularly in environments with light to medium traffic. The flooring is ideal for spaces such as healthcare settings, education facilities, and offices, where durability and ease of maintenance are key considerations. Its modern matt finish and PUR surface treatment make it easy to clean and maintain over time. The product can be installed as sheets or tiles, with the 2-meter wide rolls being 20 meters long. In terms of performance, Mipolam Classic 2 mm offers excellent durability, with a wear layer of 2 mm thickness, and meets the European classification for commercial (34) and light industrial (43) applications. It also complies with safety standards, including reaction to fire rating of Bfl-s1 and slip resistance of R9 The flooring also supports healthy indoor air quality with a TVOC level of less than 10 µg/m³ after 28 days Additionally, Mipolam Classic 2 mm is made from 25% recycled content and is fully recyclable, making it a more sustainable choice for flooring	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443	DESCRIPTION: High-performance multi-purpose floor, directional design, PUR surface treatment. A homogeneous floor for all uses with acoustics, slip resistance, and fire-rating. Homogeneous high-performance floors FLOORSCORE certification that allows access to the LEED rating system Mandatory BCRA anti-slip certification for flooring installed in public buildings Normal/Average Traffic Surface with matte finish PUR surface treatment: facilitates maintenance, does not require waxing for the entire life cycle of the product Color palette: 18 directional colors TVOC after 28 days < 10µg/m3 => indoor air quality	
SAMPLE PHOTO	UNIT DIMENSIONS: 2 m X 20.0 m	
	SPECIAL INSTRUCTIONS: Installation: Surface Preparation: Ensure that the substrate is clean, dry, and free from any contaminants before installation Adhesive: Use a suitable adhesive recommended by the manufacturer, such as a pressure-sensitive or full-spread adhesive, depending on the environment Seams: Properly weld the seams to maintain the integrity of the flooring and prevent water or dirt infiltration Acclimatization: Let the flooring acclimate to the room temperature for at least 24 hours before installation to avoid expansion or contraction Maintenance: Cleaning: Regular cleaning should be done using a neutral pH detergent. Avoid harsh chemicals or abrasive materials that can damage the surface Waxing or Polishing: It is not recommended to wax or polish the surface, as this can make it slippery and may alter its appearance Stain Removal: For tougher stains, a diluted solution of ammonia and water may be used, but always follow up with thorough rinsing Caution: Ensure the flooring is not exposed to extreme temperatures during installation to prevent shrinkage or expansion After installation, allow the flooring to rest for 24 hours before any heavy use or furniture placement	
	DATE ORDERED: 12/4/2024	
	DATE SHIPPED: TBD	
	UNIT COST: £9.99 per square meter	EST. COST: £44.96 (excluding VAT)
	# UNITS:	FRIEGHT: TBD
		TOTAL COST:

			1 box contains 50 tiles, each measuring 300x300mm	£44.96 (excluding VAT) per box
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 ☐ NFPA 255 ☐ UL #723 ☐ UFAC#8 1 ☐ NFPA 260a ☐ UFAC Class 1 ☐ UBC #8-1 rated	☐ NFPA 701 ☐ ASTM D6413.	☐ Class A - Corridors, Exits and Public areas ☒ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☒ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☐ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: 25%	Life span expectancy: 15-20yrs
			Percentage of post-industrial content: 25%	

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT VARIES/ ACCENT COLOR			ITEM REFERENCE # SW 6226	
MANUFACTURER: SHERWIN-WILLIAMS CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: 5gallons	DATE: 12/4/2024
			APPLICATION: Apply at temperatures above 50°F. Do not thin. Apply two coats by; Brush: Use a nylon-polyester brush. Roller: Use a 1/4 to 3/4 inch nap synthetic cover. Do not apply by airless sprayer DESCRIPTION: LANGUID BLUE Paint Shield® Interior Latex Eg-Shel Microbicial This gentle blue is the perfect backdrop for a lazy Sunday with loved ones. Slow down life's hasty pace with this cool neutral in your living room or bedroom. Paint Shield® Microbicial Paint is the first EPA-registered paint that kills greater than 99.9% of Staph (<i>Staphylococcus aureus</i>), MRSA, <i>E. coli</i> , VRE, and <i>Enterobacter aerogenes</i> within two hours of exposure on a painted surface.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: N/A	
			SPECIAL INSTRUCTIONS: Required; 2 coats of paint over a primer for new construction or 2 coats of paint over previously painted sound surfaces. On Drywall: Use Latex Drywall Primer, or equivalent On Masonry: Use Loxon® Concrete & Masonry Primer, or equivalent On Block: Use Loxon® Block Surfer, or equivalent On Plaster: Use Loxon® Concrete & Masonry Primer, or equivalent On Wood: Use Premium Wall & Wood Primer, or equivalent For use on hard, non-porous interior ceilings, walls, doors, and trim in nursing homes, assisted living facilities or other group homes, day care centers, doctor & dentist offices, and non-critical areas of hospitals such as waiting rooms, examination rooms, hallways and walkways. For use in residences, offices, commercial facilities, universities, colleges, dorm rooms, and health clinics. Do not use on floors or on exterior surfaces.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: \$93.99/gal # UNITS: 1 5gal tub	EST. COST: \$464.95 FRIEGHT: N/A TOTAL COST: \$464.95
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
___ ASTM-84 NFPA 255 UL #723 UFAC#8 1 ___ NFPA 260a UFAC Class 1 ___ UBC #8-1 rated	___ NFPA 701 ___ ASTM D6413.	_√_ Class A - Corridors, Exits and Public areas ___ Class B or C - Offices	___ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ___ Light fastness must exceed AATCC-16a method 100 hours ___ Maintenance ordinary cleaning with mild soap and water.	___ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
√ Manufacturer located within 500 miles ___ Rapidly Renewable _√_ Greenguard certified ___ FSC certified ___ EnergyStar rated ___ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-10yrs

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT VARIES/ ACCENT COLOR			ITEM REFERENCE # SW 6684	
MANUFACTURER: SHERWIN-WILLIAMS CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: 5gallons	DATE: 12/4/2024
			APPLICATION: Apply at temperatures above 50°F. Do not thin. Apply two coats by; Brush: Use a nylon-polyester brush. Roller: Use a 1/4 to 3/4 inch nap synthetic cover. Do not apply by airless sprayer DESCRIPTION: BRITTLEBRUSH Paint Shield® Interior Latex Eg-Shel Microbicial The Sherwin-Williams paint color SW 6684 Brittlebush is a vibrant, sunny yellow with warm undertones, ideal for adding energy and brightness to a space. It is often used to create focal points or add warmth in interior and exterior designs. Paint Shield® Microbicial Paint is the first EPA-registered paint that kills greater than 99.9% of Staph (<i>Staphylococcus aureus</i>), MRSA, <i>E. coli</i> , VRE, and <i>Enterobacter aerogenes</i> within two hours of exposure on a painted surface.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: N/A	
			SPECIAL INSTRUCTIONS: Required; 2 coats of paint over a primer for new construction or 2 coats of paint over previously painted sound surfaces. On Drywall: Use Latex Drywall Primer, or equivalent On Masonry: Use Loxon® Concrete & Masonry Primer, or equivalent On Block: Use Loxon® Block Surfacers, or equivalent On Plaster: Use Loxon® Concrete & Masonry Primer, or equivalent On Wood: Use Premium Wall & Wood Primer, or equivalent For use on hard, non-porous interior ceilings, walls, doors, and trim in nursing homes, assisted living facilities or other group homes, day care centers, doctor & dentist offices, and non-critical areas of hospitals such as waiting rooms, examination rooms, hallways and walkways. For use in residences, offices, commercial facilities, universities, colleges, dorm rooms, and health clinics. Do not use on floors or on exterior surfaces.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: \$93.99/gal # UNITS: 1 5gal tub	EST. COST: \$464.95 FRIEGHT: N/A TOTAL COST: \$464.95
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 ☐ NFPA 255 ☐ UL #723 ☐ UFAC#8 1 ☐ NFPA 260a ☐ UFAC Class 1 ☐ UBC #8-1 rated	☐ NFPA 701 ☐ ASTM D6413.	☒ Class A - Corridors, Exits and Public areas ☐ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☐ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☒ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-10yrs

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT VARIES/ ACCENT COLOR			ITEM REFERENCE # SW 6741	
MANUFACTURER: SHERWIN-WILLIAMS CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: 5gallons	DATE: 12/4/2024
			APPLICATION: Apply at temperatures above 50°F. Do not thin. Apply two coats by; Brush: Use a nylon-polyester brush. Roller: Use a 1/4 to 3/4 inch nap synthetic cover. Do not apply by airless sprayer DESCRIPTION: DERBYSHIRE Paint Shield® Interior Latex Eg-Shel Microbicidal The Sherwin-Williams paint color SW 6741 Derbyshire is a vibrant, sunny yellow with warm undertones, ideal for adding energy and brightness to a space. It is often used to create focal points or add warmth in interior and exterior designs. Paint Shield® Microbicidal Paint is the first EPA-registered paint that kills greater than 99.9% of Staph (<i>Staphylococcus aureus</i>), MRSA, <i>E. coli</i> , VRE, and <i>Enterobacter aerogenes</i> within two hours of exposure on a painted surface.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: N/A	
			SPECIAL INSTRUCTIONS: Required; 2 coats of paint over a primer for new construction or 2 coats of paint over previously painted sound surfaces. On Drywall: Use Latex Drywall Primer, or equivalent On Masonry: Use Loxon® Concrete & Masonry Primer, or equivalent On Block: Use Loxon® Block Surfacers, or equivalent On Plaster: Use Loxon® Concrete & Masonry Primer, or equivalent On Wood: Use Premium Wall & Wood Primer, or equivalent For use on hard, non-porous interior ceilings, walls, doors, and trim in nursing homes, assisted living facilities or other group homes, day care centers, doctor & dentist offices, and non-critical areas of hospitals such as waiting rooms, examination rooms, hallways and walkways. For use in residences, offices, commercial facilities, universities, colleges, dorm rooms, and health clinics. Do not use on floors or on exterior surfaces.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: \$93.99/gal # UNITS: 1 5gal tub	EST. COST: \$464.95 FRIEGHT: N/A TOTAL COST: \$464.95
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 ☐ NFPA 255 ☐ UL #723 ☐ UFAC#8 1 ☐ NFPA 260a ☐ UFAC Class 1 ☐ UBC #8-1 rated	☐ NFPA 701 ☐ ASTM D6413.	☒ Class A - Corridors, Exits and Public areas ☐ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☐ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☒ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-10yrs

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT VARIES/ ACCENT COLOR			ITEM REFERENCE # SW 6866	
MANUFACTURER: SHERWIN-WILLIAMS CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: 5gallons	DATE: 12/4/2024
			APPLICATION: Apply at temperatures above 50°F. Do not thin. Apply two coats by; Brush: Use a nylon-polyester brush. Roller: Use a 1/4 to 3/4 inch nap synthetic cover. Do not apply by airless sprayer DESCRIPTION: HEARTTHROB Paint Shield® Interior Latex Eg-Shel Microbicial The Sherwin-Williams paint color SW 6866 Heartthrob is a vibrant, sunny yellow with warm undertones, ideal for adding energy and brightness to a space. It is often used to create focal points or add warmth in interior and exterior designs. Paint Shield® Microbicial Paint is the first EPA-registered paint that kills greater than 99.9% of Staph (<i>Staphylococcus aureus</i>), MRSA, <i>E. coli</i> , VRE, and <i>Enterobacter aerogenes</i> within two hours of exposure on a painted surface.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: N/A	
			SPECIAL INSTRUCTIONS: Required; 2 coats of paint over a primer for new construction or 2 coats of paint over previously painted sound surfaces. On Drywall: Use Latex Drywall Primer, or equivalent On Masonry: Use Loxon® Concrete & Masonry Primer, or equivalent On Block: Use Loxon® Block Surfacers, or equivalent On Plaster: Use Loxon® Concrete & Masonry Primer, or equivalent On Wood: Use Premium Wall & Wood Primer, or equivalent For use on hard, non-porous interior ceilings, walls, doors, and trim in nursing homes, assisted living facilities or other group homes, day care centers, doctor & dentist offices, and non-critical areas of hospitals such as waiting rooms, examination rooms, hallways and walkways. For use in residences, offices, commercial facilities, universities, colleges, dorm rooms, and health clinics. Do not use on floors or on exterior surfaces.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: \$93.99/gal # UNITS: 1 5gal tub	EST. COST: \$464.95 FRIEGHT: N/A TOTAL COST: \$464.95
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 ☐ NFPA 255 ☐ UL #723 ☐ UFAC#8 1 ☐ NFPA 260a ☐ UFAC Class 1 ☐ UBC #8-1 rated	☐ NFPA 701 ☐ ASTM D6413.	☒ Class A - Corridors, Exits and Public areas ☐ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☐ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☒ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-10yrs

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT VARIES/ ACCENT COLOR			ITEM REFERENCE # SW 6258	
MANUFACTURER: SHERWIN-WILLIAMS CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: 5gallons	DATE: 12/4/2024
			APPLICATION: Apply at temperatures above 50°F. Do not thin. Apply two coats by; Brush: Use a nylon-polyester brush. Roller: Use a 1/4 to 3/4 inch nap synthetic cover. Do not apply by airless sprayer DESCRIPTION: TRICORN BLACK Paint Shield® Interior Latex Eg-Shel Microbicidal The Sherwin-Williams paint color SW 6258 Tricorn Black is a vibrant, sunny yellow with warm undertones, ideal for adding energy and brightness to a space. It is often used to create focal points or add warmth in interior and exterior designs. Paint Shield® Microbicidal Paint is the first EPA-registered paint that kills greater than 99.9% of Staph (<i>Staphylococcus aureus</i>), MRSA, <i>E. coli</i> , VRE, and <i>Enterobacter aerogenes</i> within two hours of exposure on a painted surface.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: N/A	
			SPECIAL INSTRUCTIONS: Required; 2 coats of paint over a primer for new construction or 2 coats of paint over previously painted sound surfaces. On Drywall: Use Latex Drywall Primer, or equivalent On Masonry: Use Loxon® Concrete & Masonry Primer, or equivalent On Block: Use Loxon® Block Surfacers, or equivalent On Plaster: Use Loxon® Concrete & Masonry Primer, or equivalent On Wood: Use Premium Wall & Wood Primer, or equivalent For use on hard, non-porous interior ceilings, walls, doors, and trim in nursing homes, assisted living facilities or other group homes, day care centers, doctor & dentist offices, and non-critical areas of hospitals such as waiting rooms, examination rooms, hallways and walkways. For use in residences, offices, commercial facilities, universities, colleges, dorm rooms, and health clinics. Do not use on floors or on exterior surfaces.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: \$93.99/gal	EST. COST: \$464.95
			# UNITS: 1 5gal tub	FRIEGHT: N/A TOTAL COST: \$464.95
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 ☐ NFPA 255 ☐ UL #723 ☐ UFAC#8 1 ☐ NFPA 260a ☐ UFAC Class 1 ☐ UBC #8-1 rated	☐ NFPA 701 ☐ ASTM D6413.	☒ Class A - Corridors, Exits and Public areas ☐ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☐ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☒ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-10yrs

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT WALL, FURNITURE/EQUIPMENT, COLUMNS			ITEM REFERENCE # F3774	
MANUFACTURER: CORIAN DESIGN			AMOUNT/QUANTITY: 30 units	DATE: 12/4/2024
CONTACT: Online Contact Us – Corian® Design 8004CORIAN SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443			APPLICATION: The Corian® Solid Surface Pebble Lane is a versatile and aesthetically unique material, ideal for both residential and commercial applications. Its distinctive design features large, randomly distributed particles that mimic the natural look of a pebbled pathway, giving each installation a one-of-a-kind appearance. This surface offers both beauty and durability, making it suitable for a variety of applications, including countertops, vanity tops, and wall surfaces. DESCRIPTION: Corian® Solid Surface is an advanced composite product used as an architectural and design material in a variety of residential and commercial applications. Corian® Solid Surface offers design versatility, functionality and durability. Supplied in sheets and shapes, it can be fabricated with conventional woodworking tools into virtually any design. It is the original Solid Surface material made only by DuPont. It is widely accepted as a material for countertops, vanity tops, tub/shower walls, kitchen sinks, vanity basins and laboratory bench tops in numerous markets including lodging, healthcare, banks, boutiques, restaurants.	
SAMPLE PHOTO			UNIT DIMENSIONS: ½" sheets 144"X30"	
			SPECIAL INSTRUCTIONS: Installation: It is recommended that installation of Corian® be done by a certified professional to ensure proper handling and a seamless finish. The material can be installed using mechanical fasteners, adhesives, or both, depending on the specific application. Use recommended adhesives designed specifically for Corian® surfaces to ensure strong bonding and durability. Cutting and Fabrication: Corian® can be cut, routed, and shaped to suit any design. However, it is important to follow safety guidelines and use appropriate tools, as the material is hard and may require specialized equipment for cutting. Maintenance: The surface is non-porous, which means it is easy to clean and resistant to stains . Use mild soap and water for regular cleaning. Avoid harsh chemicals or abrasives to maintain the surface's integrity. While Corian® is scratch-resistant, heavy-duty scouring pads or sharp objects should not be used directly on the surface. Seams: Seams can be almost invisible due to the properties of Corian®'s solid surface. However, it is important to have skilled installers handle the joining process to ensure a seamless look and avoid any visible joints.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: \$877.00 per unit- 30 or more	EST. COST: \$26,310
			# UNITS: 30	FRIEGHT: TBD TOTAL COST: \$26,310
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
___ ASTM-84 NFPA 255 UL #723 UFAC#8 1 ___ NFPA 260a UFAC Class 1	___ NFPA 701 ___ ASTM D6413.	___ Class A - Corridors, Exits and Public areas ___ Class B or C - Offices	___ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ___ Light fastness must exceed AATCC-16a method 100 hours	___ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.


☐ UBC #8-1 rated			☐ Maintenance ordinary cleaning with mild soap and water.	
☐ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: 6%	Life span expectancy: "Decades"
			Percentage of post-industrial content: 14%	

PROJECT TITLE: HAVEN		
PROJECT No: MASTER THESIS		
LOCATION IN PROJECT EXTERIOR AND INTERIOR CURTAIN WALLS	ITEM REFERENCE # 1271	
MANUFACTURER: SUNLINE CONTACT: Showroom: 313 W 4th Street Bridgeport, PA 19405 Showroom Hours: M - F, 8:30 am - 5:30 pm Call ahead to schedule an appointment 24/7 Sales Availability Phone: (866) 674-0913	AMOUNT/QUANTITY: 22	DATE: 12/4/2024
	APPLICATION: The Sunline Synergy Glass Walls 500 Series Frameless are typically used in architectural applications where transparency, modern aesthetics, and flexible space solutions are important. Below are some common applications for this type of product: Commercial Spaces Hospitality & Public Spaces Hotels and Resorts Healthcare Facilities Educational Institutions High-End Residential or Commercial Showcases DESCRIPTION: These glass walls are particularly valued for their sleek, contemporary look, sound-dampening qualities (when treated with the right glass thickness or acoustic treatments), and ability to create flexible, reconfigurable spaces in both commercial and residential settings. The frameless design enhances the minimalist, open feeling that many modern spaces strive for.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443	UNIT DIMENSIONS: 7'X4'	
SAMPLE PHOTO 	SPECIAL INSTRUCTIONS: To ensure the longevity and maintain the appearance of Sunline Synergy Glass Walls 500 Series Frameless , here are some special care instructions: Regular Cleaning: Use a Soft Cloth: Clean the glass surfaces regularly with a soft, lint-free cloth to remove dust and fingerprints. Mild Cleaning Solutions: Use a non-abrasive, mild glass cleaner or a mixture of water and vinegar. Avoid harsh chemicals that could damage the glass or coatings. Avoid Abrasive Materials: Do not use abrasive sponges or scrubbers, as they could scratch the glass surface. Dry After Cleaning: Use a dry cloth to wipe away excess moisture to prevent water spots from forming. Preventing Scratches: Be cautious when moving furniture or objects near the glass to avoid accidental impacts or scratches. Avoid using sharp or hard objects near the glass walls. Handling of the Frames and Hardware: Check Hardware Regularly: Ensure that the hardware (e.g., hinges, fasteners) is tight and functioning properly. Check for any loose parts or wear that may need attention. Lubrication: Periodically, apply a silicone-based lubricant to any metal parts that move or slide, but avoid overspraying onto the glass surface. Avoid Excessive Force: Do not apply excessive force to the glass walls, especially around the edges or where hardware is attached. Avoiding Excessive Moisture: While these systems are typically designed to withstand moisture, avoid direct exposure to standing water or harsh cleaning techniques that may seep into the framework. Ensure proper drainage and air circulation in areas like bathrooms or kitchens. Temperature and Humidity Control: Try to maintain a consistent indoor temperature and humidity level to prevent any warping or damage to the glass or framing system. Avoid exposing the glass to extreme temperature fluctuations (e.g., near hot pipes, stoves, or air conditioning vents). Inspection and Maintenance: Annual Inspections: It's recommended to perform regular inspections (annually) to check for any wear, chips, or cracks in the glass, as well as to ensure that the hardware is in good condition. Professional Maintenance: If necessary, hire professionals to handle any repairs or more detailed cleaning, especially if the glass is in hard-to-reach areas.	

			By following these care instructions, you can maintain the aesthetic appeal and functionality of your Sunline Synergy Glass Walls 500 Series Frameless system for many years.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: \$175.00	EST. COST: \$3,850
			# UNITS: 22	FRIEGHT: TBD TOTAL COST: \$3,850
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 ☐ NFPA 255 ☐ UL #723 ☐ UFAC#8 1 ☐ NFPA 260a ☐ UFAC Class 1 ☐ UBC #8-1 rated	☒ NFPA 701 ☒ ASTM D6413.	☐ Class A - Corridors, Exits and Public areas ☐ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☐ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☒ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☒ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 20-40yrs

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT WALLS/ FLOORS/FURNITURE			ITEM REFERENCE # NOT SPECIFIED	
MANUFACTURER: PORTERCRAFT CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: NA	DATE: 12/4/2024
			APPLICATION: Suitable for residential and commercial flooring installations. DESCRIPTION: The Hudson Collection Dark Hardwood is a premium flooring material known for its rich tones, durability, and timeless aesthetic. This hardwood is crafted from high-quality, sustainably sourced wood species such as oak, walnut, or hickory, offering a deep, elegant finish that enhances any space. The Hudson Collection Dark Hardwood combines elegance and durability, making it an excellent choice for those looking to enhance their interiors with a warm yet modern aesthetic.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: Width:4in, Length:varies, Thickness:3/4in	
			SPECIAL INSTRUCTIONS: Acclimate the flooring in the installation area for at least 72 hours prior to installation. Ensure the subfloor is clean, dry, and level. Follow the manufacturer's installation guidelines for optimal results..	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: varies # UNITS: n/a	EST. COST: FRIEGHT: N/A TOTAL COST:
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 ☐ NFPA 255 ☐ UL #723 ☐ UFAC#8 1 ☐ NFPA 260a ☐ UFAC Class 1 ☐ UBC #8-1 rated	☐ NFPA 701 ☐ ASTM D6413.	☒ Class A - Corridors, Exits and Public areas ☐ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☐ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☒ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-10yrs

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT FITNESS CENTER			ITEM REFERENCE # MOMENTUM 41 ARTIFICIAL TURF	
MANUFACTURER: SHAW SPORTS TURF CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: NA	DATE: 12/4/2024
			APPLICATION: Suitable for indoor and outdoor recreational spaces, multipurpose community centers, sports fields, and landscaping. DESCRIPTION: The Momentum 41 Artificial Turf by Shaw Sports Turf is a durable, realistic synthetic grass designed for high-traffic areas. It features a polyethylene fiber blend that mimics the look and feel of natural grass while providing enhanced durability and weather resistance. The backing system offers superior drainage, and the turf is available with anti-microbial treatments to prevent odors and bacteria buildup.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: Available in 15 ft width rolls with customizable lengths.	
			SPECIAL INSTRUCTIONS: Installation: Requires proper drainage preparation and professional installation for optimal performance. Maintenance: Regular brushing and occasional rinsing to maintain appearance and longevity. Safety: Ensures proper infill to provide cushioning and traction.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: typically \$3.50 - \$7 per sq. ft. # UNITS: 1 roll	EST. COST: FRIEGHT: N/A TOTAL COST:
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
☐ ASTM-84 NFPA 255 UL #723 UFAC#8 1 ☐ NFPA 260a UFAC Class 1 ☐ UBC #8-1 rated	☐ NFPA 701 ☐ ASTM D6413.	☐ Class A - Corridors, Exits and Public areas ☐ Class B or C - Offices	☐ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ☐ Light fastness must exceed AATCC-16a method 100 hours ☐ Maintenance ordinary cleaning with mild soap and water.	☒ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
☒ Manufacturer located within 500 miles ☐ Rapidly Renewable ☒ Greenguard certified ☐ FSC certified ☐ EnergyStar rated ☐ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-12yrs with proper care

PROJECT TITLE: HAVEN				
PROJECT No: MASTER THESIS				
LOCATION IN PROJECT FLOORING IN MOVIE ROOM			ITEM REFERENCE # LATEST TREND 00800 DARK RED NYLON CARPET	
MANUFACTURER: PHILADELPHIA COMMERCIAL CONTACT: Mon-Fri: 8:30 AM - 6:00 PM EST Sat: 9:00 AM - 5:00 PM EST Monday To Friday 8:30 AM To 6:00 PM EST Saturday 9:00 AM To 5:00 PM EST 1-800-474-3794			AMOUNT/QUANTITY: NA	DATE: 12/4/2024
			APPLICATION: Suitable for commercial settings such as offices, corridors, and public areas. DESCRIPTION: The Latest Trend 00800 Dark Red Nylon Carpet by Philadelphia Commercial is a high-quality, durable carpet designed for commercial use. Its dark red hue adds a touch of sophistication to any space, while the nylon construction ensures resilience and longevity. The pattern finish enhances its aesthetic appeal, making it suitable for various interior designs.	
SHIP TO: 1025 SW 112 th Ave, Miami, FL 33174 CONTACT: (540)200-5443				
SAMPLE PHOTO 			UNIT DIMENSIONS: 12 ft x 220 ft	
			SPECIAL INSTRUCTIONS: Ensure proper installation by a certified professional to maintain warranty and performance standards.	
			DATE ORDERED: 12/4/2024	
			DATE SHIPPED: TBD	
			UNIT COST: varies	EST. COST:
			# UNITS: 1 roll	FRIEGHT: N/A TOTAL COST:
Flame/Smoke Tests met			Performance Tests met	
Upholstery Fabrics	Window Treatments	Wall, Floor, and Ceiling Finish	Upholstery Fabrics	Hard Surface Tile or Stone
___ ASTM-84 NFPA 255 UL #723 UFAC#8 1 ___ NFPA 260a UFAC Class 1 ___ UBC #8-1 rated	___ NFPA 701 ___ ASTM D6413.	_✓_ Class A - Corridors, Exits and Public areas ___ Class B or C - Offices	___ Abrasion resistance - must exceed the Wyzenbeek Test (ASTM D-3597) 50,000 rubs ___ Light fastness must exceed AATCC-16a method 100 hours _✓_ Maintenance ordinary cleaning with mild soap and water.	___ Non-slip finish with minimum static coefficient of friction of .6 per ASTM 1028 is required in guestrooms and bathrooms.
___ Manufacturer located within 500 miles ___ Rapidly Renewable ___ Greenguard certified ___ FSC certified ___ EnergyStar rated ___ WaterSense Certification			Percentage of post-consumer content: N/A Percentage of post-industrial content: N/A	Life span expectancy: 8-10yrs depending on maintenance and foot traffic